



DECLARATION OF CONFORMITY

Manufacturer: Kiili Betoon LLC

The product has a warranty for 2 years.

The products of exposed aggregate concrete have the following qualifications:

- | | |
|--|--|
| 1. Compressive strength N, mm ² | ≥ Mpa 35, standard EVS-EN 12390-3:2009 |
| 2. Concrete class | C30/37, standard EVS-EN 206-1:2007 |
| 3. Frost resistance class S, kg/m ² | KK4 (56 cycles), standard EVS 814:2003 |
| 4. Durability | ≥ LA 20 |
| 5. Allowable deviations | (+/-)mm |
| length | 10 mm |
| width | 10 mm |
| height | 5 mm |

The composite mixture used in producing slabs of exposed aggregate concrete has a fixed consistency that corresponds to the rules of the mixing procedure. The concrete mix is blended in the liquidizer using the following raw materials:

1. Granite rubble – grey, fraction 2-8 mm – the product conforms to the standard documentation EVS-EN 12620; production control certificate No. 0416-CPD-0013/SFS
2. Sand – quartz, fraction 0/4 – the product conforms to the standard documentation EVS EN 12620:2003; production control certificate No. 1403-CPD-0001
3. Portland cement – grey, CEM 142,5 – the product conforms to the standard documentation EVS-EN 197-1:2002; EU- certificate of conformity No. 1504-CPD-022/05

Amplification – mark: BSt 500M – quality certificate No. 306 DIN EN 10204:2005-01.

Kiili Betoon LLC
Vaela, Kiili Parish 75401, Harjumaa, Estonia
Phone: +372 6725591
E-mail: info@kiilibetoon.ee